


REBITES DE ALUMÍNIO COM MANDRIL DE ALUMÍNIO

Rebites padrão (cabeça abaulada)

Corpo: alumínio liga 5005, NATURAL

Mandril: alumínio, polido



Linha	Rebite (D x L) mm	Código (embalagem)	Diâmetro corpo +0,08 - 0,10 mm	Comprimento corpo +0,8 - 0,2 (mm)	Espessura Rebitável (mm)	Diâmetro Aba (mm)	Tração (kgf)	Cisalhamento (kgf)
3,2 Dia.furo 3,3 mm	3,2 x 5,5	6330504.01000	3,2	5,5	1,0 - 3,0	6,3 +0,5 - 0,3	64	46
	3,2 x 6,5	6330720.01000		6,5	1,5 - 3,5			
	3,2 x 08	6331027.01000		8,0	3,5 - 5,0			
	3,2 x 10	6331427.01000		10,0	5,0 - 7,0			
	3,2 x 12	6331829.01000		12,0	6,5 - 8,5			
4,0 Dia.furo 4,1 mm	4,0 x 08	*	4,0	8,0	3,0 - 5,0	7,5 +0,5 - 0,3	108	79
	4,0 x 10	*		10,0	5,0 - 6,5			
	4,0 x 12	*		12,0	6,5 - 8,0			
	4,0 x 15	*		15,0	8,0 - 11,0			
	4,0 x 18	*		18,0	11,5 - 14,0			
4,8 Dia.furo 4,9 mm	4,8 x 08	*	4,8	8,0	2,5 - 4,0	9,3 +0,5 - 0,3	153	107
	4,8 x 10	*		10,0	4,0 - 6,0			
	4,8 x 12	*		12,0	6,0 - 8,0			
	4,8 x 14	*		14,0	8,0 - 10,0			
	4,8 x 16	*		16,0	10,0 - 12,0			
	4,8 x 18	*		18,0	12,0 - 13,5			
	4,8 x 24	*		24,0	16,0 - 19,0			
6,2 Dia.furo 6,3 mm	6,2 x 10	*	6,2	10,0	3,0 - 5,0	11,0 +0,7 - 0,5	293	208
	6,2 x 12	*		12,0	5,0 - 7,0			
	6,2 x 14	*		14,0	6,0 - 8,0			
	6,2 x 16	*		16,0	8,0 - 10,0			
	6,2 x 18	*		18,0	10,0 - 12,0			
	6,2 x 22	*		22,0	12,0 - 16,0			
	6,2 x 25	*		25,0	16,0 - 19,0			
	6,2 x 30	*		30,0	19,0 - 24,0			

* consulte

** para outras medidas, materiais e cores: consulte nossa equipe